


stop crime fast with the

SENTINEL S70

SLIMLINE | POWERFUL | VERSATILE | BRILLIANT



sen-ti-nel n. A guard whose job it is the stand and keep watch

Suitable for a wide range of applications

Quality assured performance and reliability

Simple installation and integration

The Smoke Screen Sentinel range has been designed and manufactured for permanent installation either as a fully integrated part of an intruder alarm system or as a stand-alone system. The range comprises some of the most advanced security smoke generators in the world.

The new, precision engineered steel block and state of the art cartridge heaters offer a higher level of performance and reliability. This translates to a more impressive volume of drier fog that lasts for even longer.

The Sentinel S70 is designed to be installed in almost any configuration. Its compact size and impressive performance make this the workhorse of the range, suitable for almost any application: shops, offices, workshops, service stations, jewellers - anywhere fast acting thieves may strike. New PCB technology, ergonomic connectors and multi-bracket design make installation easy and straightforward. Other features such as the internal battery back-up and a larger fluid capacity make the S70 incredibly versatile.



'ANTI-RAID' FIRST BURST

Turbo mode for maximum smoke generation in risk critical areas designed to stop thieves in their tracks.

VERSATILITY IS KEY

Machined steel heater block allows use of the most persistent smoke chemical. Powerful performance and compact size make it ideal for any application.

MULTI-NOZZLE OPTIONS

A range of different nozzles are available to produce a range of different effects. This makes installation even easier.

FEATURES

- 5-year warranty. Full heater redundancy protects against critical failure.
- Turbo mode for maximum smoke generation in risk critical areas.
- Min. 1 hour off-mains operational capability.
- Energy save mode cuts costs when generator is not immediately needed.
- IP interface available.
- Supports automatic re-firing via screen-sensor technology.
- Extreme temperature operation: -10°C to 50°C.
- £10 million product and public liability insurance.

OPERATION

- 4 inputs and 7 outputs.
- LCD status display and on-board event log.

CONSTRUCTION

- Rugged and compact steel casing in white/black.
- Environmental pack for installation in confined spaces with elevated ambient temperatures.
- Machined steel heater block allows use of most persistent smoke chemical.

STANDARDS COMPLIANCE

- EN50131:8 and IEC62642:8.
- CNPP Rating: Class I Category 30.

FLUID

- 500ml/1,000ml/5,000ml fluid system.

DATA

- 46.5(H)* x 13(D) x 31(W) cm *add 0.5cm for feet.
- Weight: 14kg (pre-install), 19kg (installed).

CAN'T SEE IT? CAN'T STEAL IT!